

CHIPREG MFC Mass Flow Controller

- Ultra compact size < 22mm
- High turndown ratio
- Best performance-to-cost ratio
- Fast time-to-market through complete sub-assemblies
- Analytical clean version available
- No drift, no recalibration required
- For industrial gas flow regulation, precision laser marking, bioreactors, analytical, medical devices and process control applications



Technical features

Sensor:
Thermal MEMS sensor

Flow ranges:
0-0,2 l_s/min
0-0,5 l_s/min
0-1 l_s/min
0-2 l_s/min
0-5 l_s/min
0-10 l_s/min
0-20 l_s/min
Higher and lower flows on request

Operating gas:
Air, N₂, O₂, CO₂, Ar, neutral gas

Accuracy*:
± 0,2% of full scale (0-10% of max flow)
± 2,0% of reading (10%-100% of max flow)

Dynamic range:
Standard: 500:1
Premium: 1000:1 (for 0-200 ml_s/min only)

Response time:
As fast as 100 ms
No warm-up time

Thermal sensitivity:
± 0,004% of full scale per °C (0-10% of max flow)
± 0,04% of reading per °C (10-100% of max flow)

Operating pressure:
Vacuum - 8 barg (details provided in 'Standard Models' below)

Repeatability:
< 1% of reading

Operating voltage:
24 V d.c. ± 10%

Current supply:
< 100 mA

Electrical connection:
JST Connector BM06B-GHS-TBT

In & output signals:
Analog 0 ... 5 V d.c. & RS485
Analog 0 ... 5 V d.c. & RS232

Digital communication protocol:
IMI FAS proprietary protocol & Modbus RTU

Weight:
125g

Pneumatic connections:
In line version (G1/8")
Manifold mount

Seal material:
FPM

Gas temperature:
+10 ... +50°C (+50 ... +122°F)

Ambient temperature:
+10 ... +50°C (+50 ... +122°F)

Additional options:
USP class VI seals, stainless steel manifold for bioreactors

* Calibrated under standard conditions: 20°C, P=1 atm. Custom calibration conditions on demand. Accuracy does not include reference error.

Technical data – standard models

Flow range	Max. operating pressure	Port type	Digital Communication Interface	kv *1)	Model
(l _v /min)	(barg)				
0 ... 0,2	8	G 1/8	RS485	0,02	8582002CJ28111110000
0 ... 0,5	8	G 1/8	RS485	0,02	8585002CJ28111110000
0 ... 1	8	G 1/8	RS485	0,02	8580011CJ28111110000
0 ... 2	5	G 1/8	RS485	0,12	8580021CJ28111110000
0 ... 5	5	G 1/8	RS485	0,12	8580051CJ28111110000
0 ... 10	4	G 1/8	RS485	0,55	8580101CJ28112110000*2)
0 ... 20	4	G 1/8	RS485	0,55	8580201CJ28112110000

*1) Cv = 0,07 kv

*2) This model enables higher flows at lower pressures than above.

Electrical connection
(optional)

Electrical connector
JST GHR-06V-S
with 300 mm flying leads



S401.0024

Cable starter kit
(optional)

USB to JST cable (incl. RS485 converter)
Power supply, universal input voltage and interchangeable AC blades for global use



S401.0305

Codification and option selector

		858*****C*****11*****000											
Flow range *3)	Substitute											Calibration gas	Substitute
0 ... 200 ml _s /min	2002											Calibrated with air, k-factor for other gas	0
0 ... 500 ml _s /min	5002											Calibrated with specific gas	1
0 ... 1 l _s /min	0011											Dynamic range	Substitute
0 ... 2 l _s /min	0021											Standard, 500:1	1
0 ... 5 l _s /min	0051											Premium, 1000:1	2
0 ... 10 l _s /min	0101											Cleanliness	Substitute
0 ... 20 l _s /min	0201											Standard	1
Higher or lower flows on request												Analytical clean	2
Electric interface	Substitute											Valve *5)	Substitute
RS232 + IN 0 ... 5V + OUT 0 ... 5V	G											Standard	1
RS485 + IN 0 ... 5V + OUT 0 ... 5V	J											Only for high flow models (kv of 0,55)	2
Mounting	Substitute												
Manifold mount	1												
Inline G1/8"	2												
Media *4)	Substitute												
Nitrogen (N ₂), Oxygen (O ₂), Air	8												
On request:													
Carbon Dioxide (CO ₂)	3												
Argon (Ar)	5												

*3) Flow range of the calibration gas

*4) See gas flow equivalency table below

*5) Standard options are calibrated at 4 barg while high flow models (kv 0,55) are calibrated at 3 barg.
Inlet pressure sensitivity:
≈ -0,6% / bar reading (air)
≈ -1,3% / bar reading (CO₂)

Gas flow equivalency table – flow range


Media	Air / N ₂ / O ₂	CO ₂	CO ₂	Ar	Ar
Units	MFC calibrated with air	MFC calibrated with CO ₂	MFC calibrated with air	MFC calibrated with Ar	MFC calibrated with air
(ml _s /min)	200	100	100	200	187
(ml _s /min)	500	250	236	450	446
(l _s /min)	1	0,5	0,532	1	0,892
(l _s /min)	2	1	0,97	2	1,78
(l _s /min)	5	2,5	2,43	5	4,46
(l _s /min)	10	5	4,93	8	8,06
(l _s /min)	20	10	9,72	15	15,9
Additional accuracy error when calibrated with air	0	0	± 8% of reading	0	± 8% of reading

When switching from one gas to another in a single MFC, it is common practice to ensure the system is fully flushed with new gas before starting precise control.


Maximum Flow Rate

Flow rate may be limited by inlet pressure.
Please ensure your inlet pressure is high enough to achieve your desired maximum flow rate as per below curves.


Typical data for air at 20°C



Typical data for air at 20°C




Block diagram



Dimensions

Manifold mount


Dimensions in mm
Projection/first angle



- 1 $\varnothing$ 3,6 mm through hole (2x)
- 2 Connector JST BM06B-GHS-TBT (First pin on the left)
- 3 INLET $\varnothing$ 4 mm
- 4 OUTLET $\varnothing$ 4 mm
- 5 $\varnothing$ 13 (2x) sealing area /Ra 0,8

Electrical connection


Pin#	Description (RS232)	Description (RS485)
1	+24V	+24V
2	Ground	Ground
3	Rx	A
4	Tx	B
5	Analog flow out	Analog flow out
6	Analog flow setpoint	Analog flow setpoint



Dimensions

Inline version (G1/8")


Dimensions in mm
Projection/first angle



- 1 $\varnothing$ 3,6 mm through hole (2x)
- 2 Connector JST BM06B-GHS-TBT (First pin on the left)
- 6 OUTLET G1/8" Thread depth 9 mm
- 7 INLET G1/8" Thread depth 9 mm

Electrical connection

Pin#	Description (RS232)	Description (RS485)
1	+24V	+24V
2	Ground	Ground
3	Rx	A
4	Tx	B
5	Analog flow out	Analog flow out
6	Analog flow setpoint	Analog flow setpoint



Warning

These products are intended for use with aggressive sensitive media. Please contact IMI for more compatibility requests. Do not use these products where pressures and temperatures can exceed those listed under „**Technical features/data**“. Before using these products with fluids other than those specified, for non-industrial applications, life-support systems or other applications not within published specifications, consult IMI.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes.

The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure. System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.